

INDEX

Symbols

<, 28
<<, 265
>, 27–28
>>, 27–28
[, 256–261
\$, xxi, 12–13, 22, 290
##, 254
\$\$, 255
\$0, 255
\$1, 254
\$?, 255–256. *See also* exit code
\$@, 254–255
#, xxi, 13. *See also* root
#!, 249–250, 325
|, 19, 27, 39
/, 40, 93, 95–97, 99–100
*, 17–18, 21, 251–252. *See also* regular expressions

A

abstraction, 1–2
administrator. *See* root
alias, 290–291
ALSA, 53
Apache, 346
Apple partition, 73
application layer, 191, 229–232
archive, 37–39
 table of contents, 38
 testing, 38, 330–331
ARP, 225–226
at, 161
ATA, 62
autoconf, 332–336
autotools, GNU, 330, 342. *See also* autoconf
Avahi, 208, 239
awk, 266

B

basename, 265–266
bash, 12. *See also* Bourne Shell
 startup file, 292–295
bg, 32
/bin, 40
/bin/bash. *See* bash
/bin/sh. *See* Bourne Shell
BIOS, 97
 boot partition, 108
bison, 325
blkid, 76
block bitmap, 90
blockdev, 70
block device, 46–48, 53, 61, 63,
 65–67, 70
/boot, 41, 102–103
boot, 93–94. *See also* init
 loader, 93, 97–98
 chainloading, 106–107
 filesystem access, 97, 101–102
 GRUB, 102
 internals, 107–109
 multi-stage, 107
 for systems other than Linux,
 106–107
 messages, 94–95
 network configuration, 202–203
Bourne Shell, 12
 basic use, 12–13
 Bourne-again, 12
 script (*see* shell script)
building software, 330–333, 340–342
bunzip2, 39
bus error, 30
BusyBox, 349
bzip2, 39

C

- C, 310–311
 - compiler, 320–321, 340–341
 - preprocessor, 312–313, 321, 335, 341–342
- case, 262
- cat, 13
- cd, 16–17
- chainloading, 106–107
- character device, 46–47, 53
- child process, 175
- Chrome OS, 308
- chsh, 12, 21, 166–168
- chvt, 52, 300
- CIDR, 195
- clang, 310
- CLASSPATH, 327
- clobber, 27
- cloud computing, 348
- CMake, 331, 342
- command-line editing, 24
- command substitution, 263–264
- compiling, 310–311
- compositing window manager, 305
- compressing files, 37–39, 277
- concatenating files, 13
- configuration file, 40, 149–150
- configure, 332–336
- context switch, 5–6
- control group, 123
- controlling terminal, 51
- coreboot, 98
- coreutils, 332–333, 338
- cp, 15
- cpio, 146
- cpp, 312–313, 321, 335, 341–342
- CPU, 2–4
 - multiple, 6, 176
 - time, 171–172, 178–181, 183–185
- CPU time, 32
- cron, 159–161
- csh, 294
- CTRL-C, 14
- CTRL-D, 13–14
- CUPS, 307–308
- curl, 230–232
- current working directory, 16, 19–20, 172–173
- cylinder, 71–72

D

- daemon, 149
- database, 346–347
- date, 157–158
- D-Bus (Desktop Bus), 58, 124–125, 203, 299, 305–307
 - instance, 306
 - monitoring, 306–307
- dd, 48–49, 83
- debugfs, 84
- debugger, 323–324
- default gateway, 196, 201
- demand paging, 182
- desktop, 297–298
 - background, 304
 - environment, 299
- Desktop Bus. *See* D-Bus
- /dev*, 40, 46–48
- device, 45
 - audio, 53
 - block, 46–48, 53, 61, 63, 65–67, 70
 - character, 46–47, 53
 - copy, 48–49
 - creating file, 53–54
 - disk, 46–48
 - driver, 4, 7, 93
 - file, 40, 46–47, 53–57, 80
 - finding, 48–49
 - information, 47–48, 57–58
 - initialization, 53–58
 - major and minor numbers, 47–49
 - monitor, 57–58
 - name, 47–53
 - network, 47
 - node, 40, 46–47, 53–57, 80
 - optical, 51, 63–64, 73
 - parallel, 52
 - pipe, 47, 53
 - SCSI (*see* SCSI)
 - serial, 52
 - socket, 47, 247–248
 - terminal, 51–52
 - types, 46–47
- /dev/hd**, 51
- /dev/lp**, 52
- /dev/null*, 46
- /dev/parport**, 52
- /dev/pts*, 51
- /dev/sd**, 50–51

- /dev/sg**, 51, 63–64
- /dev/snd*, 53
- /dev/sr**, 51, 63–64
- devtmpfs, 53–55
- /dev/tty**, 51–52
- /dev/zero*, 48–49
- df, 81
- DHCP, 214–215
- diff, 20, 256, 339
- directory, 16, 33
 - change, 16–17
 - create, 17
 - current, 16, 19–20, 172–173
 - errors, 30
 - hierarchy, 16, 40–42
 - home, 17, 40, 154–155
 - internal structure, 88
 - listing contents, 14–15
 - parent, 16, 88–90
 - permissions, 35
 - remove, 17
 - root, 40, 93, 95–97, 99–100
- disk
 - addressing, 71–72
 - buffer, 77
 - cache, 77
 - capacity, 69
 - copy, 48–49
 - device, 50–51, 65–68
 - device file, 46–48
 - format, 68, 74–75
 - geometry, 70–72
 - monitoring usage, 183–187
 - partition (*see* partition)
 - PATA, 51
 - quota, 188
 - raw access, 48–49, 67
 - SATA, 50–51, 56, 62
 - scheduling priority, 187
 - schematic, 65–66
 - SCSI, 50–51, 59–62
 - solid-state, 72, 91
 - swap 80, 85–86
 - usage, 81
- display, 300
 - manager, 300
 - modes, 51–52
- dmesg, 49, 94–95, 153. *See also*
 - kernel: log

- DNS (Domain Name Service),
 - 198–199, 206–209
- documentation, 25–27
- Domain Name Service (DNS),
 - 198–199, 206–209
- dot file, 21, 287
- DPMS, 305
- du, 81

E

- e2fsck, 80, 82–84
- echo, 13, 16
- EDITOR, 295–296
- effective user ID (euid), 162–165
- EFI, 97–98, 105–108
 - ESP, 108–109
 - secure boot, 106
- efilinux, 98
- egrep, 18
- elapsed time, 178–179
- Emacs, 24–25
- embedded system, 348–349
- encryption, 170, 233–234
- environment variable, 21–22,
 - 268–269
- error message, 27–30, 175
- ESP, 108–109. *See also* EFI
- /etc*, 40, 149–150
- /etc/fstab*, 50, 77, 79–81
- /etc/hosts*, 207
- /etc/init.d*, 142
- /etc/inittab*, 139–141
- /etc/ld.so.cache*, 316
- /etc/ld.so.conf*, 316
- /etc/localtime*, 158
- /etc/login.defs*, 170
- /etc/mtab*, 78
- /etc/nologin*, 144
- /etc/nsswitch.conf*, 207–209, 346
- /etc/passwd*, 26, 153–155, 164–165, 346
- /etc/profile*, 292
- /etc/rc.d*, 140–142
- /etc/resolv.conf*, 207
- /etc/services*, 211
- /etc/shadow*, 154–155
- /etc/shells*, 155, 166–168
- Ethernet, 199–200, 225–226
 - wireless, 226–228
- euid (effective user ID), 162–165

exec(), 7, 174, 268
executable, 34–35, 40–41, 78,
310–311, 325
exit code, 255–257
export, 22

F

fdisk, 68–70
fg, 32–33
files, 20

- comparing with another file, 20
- compressing, 37–39, 277
- copying, 15
- creating empty, 15
- deleting, 16, 89
- descriptor, 172–173
- details, 14–15
- device, 40, 46–47, 53–57, 80
- dot, 21, 287
- errors, 29–30
- find, 20
- find text in, 18–19
- format, 20
- group, 14–15, 33–34
- identify, 259–260
- link, 36, 87–90, 260
- link count, 89–90
- listing, 14–15
- mode, 33–35
- move, 15
- open, 172–174
- owner, 14–15, 33–34
- permissions (*see* permissions)
- redirecting
 - command input from, 28
 - command output to, 27–28
- regular, 33
- rename, 15
- sharing
 - across a network, 278–286
 - with other users, 9–10
- socket, 47, 247–248
- swap, 85
- temporary, 264–265
- test, 259–260
- transferring, 271
 - with Python, 271
 - rsync, 272
 - SSH, 236–237

type, 33, 35, 46, 173
updating timestamp, 15
filesystem, 66–67, 72–73

- Btrfs, 74, 91
- capacity, 81
- check, 82–84
- CIFS, 285
- creating, 68, 74–75
- currently attached, 75–76
- ext2/ext3/ext4, 73–77, 82–84
- FAT, 73
- HFS+, 73
- hierarchy, 40–42
- internal structure, 74, 87–90
- ISO 9660, 73, 78
- journal, 73, 82–83
- mount, 75–80, 114, 130–131
 - options, 77–80
- NFS, 285–286
- proc, 40, 79–80, 84
- read-only, 78–79, 96
- remount, 79
- repair, 82–84
- tmpfs, 84
- type, 73–74
- usage, 81
- user space, 73
 - interface, 90–91
- UUID, 50, 76–77, 79, 96, 99–101

find, 20, 267–268
finding command, 25
firewall, 219–221

- rule, 221–223
- strategy, 223–224

flex, 325
for, 262
fork(), 7, 123–124, 136–137, 174, 176,
232–233

frame, 199
free, 85
fsck, 80, 82–84
FTP, 237, 245

G

gateway, 192, 196
gcc, 310
gdb, 323–324
gdisk, 68
GECOS, 154

- geteuid(), 164–165
- getty, 52, 120, 135–136, 140, 157
- Ghostscript, 308
- glob, 17–18, 21, 251–252. *See also*
 - regular expression
- GNU autotools, 330, 342. *See also*
 - autoconf
- gparted, 67–69
- GPT, 67–69, 101
- grep, 18–19, 256–257
- group, 10, 154, 156–157
 - listing, 34
 - permissions, 33–35
- groups, 34
- GRUB, 98
 - boot command, 102
 - command line, 100–101
 - configuration, 98–99, 102–104
 - devices, 100–101
 - filesystem access, 101–102
 - insmod, 99–100
 - install, 104–106
 - internals, 108–109
 - menu, 98–99, 103
 - on removable media, 105–106
 - root, 99–102
- grub-mkconfig, 103–104
- GTK+, 299
- guest operating system, 347–348
- gunzip, 37–39
- gzip, 37–39

H

- halt, 144–145
- hard link, 36, 87–90, 260
- hardware operation, 4
- head, 21, 71–72
- header file, 41, 311–312, 335, 337
 - locating, 341–342
- help, 25–27
- here document, 265
 - /home*, 40
- home directory, 17, 40, 154–155
- host, 190, 198–199
- host key, 234–236
- HTTP, 230–232
- hypervisor, 348

I

- ICMP, 197–198
- ifconfig, 193–194, 200–202
- if/then/else, 256–258
- image, 4
- include file, 311–313, 335, 336
- inetd, 237
- info, 26–27, 43
- init, 93–95, 112–113. *See also* systemd;
 - Upstart
- identifying, 114
 - process tracking, 112–113
 - runlevel, 113
 - systemd, 129
 - System V, 139–142
 - Upstart, 138–139
 - sequence, 112, 141–143
 - System V, 112–114, 129, 138–143
- initctl, 132
- initramfs, 99–100, 109, 145–146
- initrd, 146. *See also* initramfs
- inode, 82, 87–90, 260
 - root, 88–90
- installing software, 329–330, 338
- interactive shell, 292–294
- Internet layer, network, 191–192. *See also* IP
- iostat, 185–186
- iostat, 186–187
- IP, 192
 - address, 192–194, 200–202, 216–217
 - chain, 220–224
 - filter, 219–220
 - forwarding, 216
 - subnet, 192–195
 - choosing, 216–217
 - mask, 194–195, 201
 - routing between, 215–216
 - table, 220
- IPP, 307–308
- iptables, 221–224
- IPv4, 192
- IPv6, 192

J

- Java, 327–328
- job control, 32
- jobs, 32

K

- kernel, 2–5
 - as a resource, 171
 - boot, 93, 95–96
 - boot messages, 94–95
 - compiling, 343
 - disk buffer, 77
 - disk cache, 77
 - disk I/O system, 66–67, 86
 - load, 93, 97–98
 - location, 42
 - log, 58–59, 153
 - modules, 42
 - network interface, 47, 200–203
 - parameters, 96–97, 99–100
 - reading partition table, 69–70
 - ring buffer, 94
 - routing table, 196
 - SCSI subsystem, 58–64
- kernel mode, 3
- kernel space, 3
- keyboard, 302–304
- kill, 31–32

L

- LAN, 190
- layer, 2
 - network, 189–192
- LBA, 71–72, 97
- LDAP, 346
- ldconfig, 316
- ldd, 315–316
- LD_LIBRARY_PATH, 296, 316–317
- ld.so, 315–316
- less, 19, 293–294, 296, 336
- level, 2
 - in user space, 8–9
- Lex, 324–325
 - /lib*, 40
- libata, 60, 62
- library, 40, 336–337
 - linking against, 313–314, 316–317, 321
 - shared, 40, 314–317, 334–335, 337
 - system calls, 174–175
 - trace, 176
- LILO, 98

link

- count, 89–90
- farm, 142
- hard, 36, 87–90, 260
- symbolic, 35–36
- listen, 210–211, 239–240
- literal, 251–253
- LLVM, 310, 328
- ln, 35–36, 87, 89–90
- loadable kernel modules, 42
- load average, 180–181
- LOADLIN, 98
- localhost, 205, 209
- locate, 20
- log, 9. *See also* kernel, log; syslog
 - kernel, 58–59, 153
 - syslog, 150–153
 - system, 121
 - Upstart, 134, 138
- logger, 153
- login, 157
- login shell, 292–294
- logrotate, 153
- loops, 262–263
- lost+found*, 83, 90
- ls, 14–15
- lsuf, 172–174
 - network, 239
 - Unix domain socket, 248
- lsscsi, 50, 59, 63
- lsusb, 62
- ltrace, 176

M

- MAC address, 199–200, 205–206, 225–226
- main memory. *See* memory
- make, 318–323
- Makefile
 - dependency, 318–319, 323
 - organization, 322–323
 - rule, 318–319
 - separator, 319–320
 - staying up-to-date, 320
 - target, 318–319
 - standard 322, 336
- man, 25–26. *See also* manual page
- manual page, 25–27, 42, 290

- MBR, 67–69, 101
 - boot, 107–108
- mDNS, 208
- /media, 41
- memory, 3–4
 - capacity, 85–86, 181
 - insufficient, 84, 86, 181
 - management, 6, 95, 182–183
 - monitoring usage, 183–185
 - page, 182
 - protection, 3
 - swap, 80, 85–86
 - partitions, 68–69, 85
 - test, 104
 - virtual, 6, 85
- Mir, 305
- mkdir, 17
- mkfs, 74–75
- mknod, 53–54
- mkswap, 85
- MMU, 6, 182
- modules, kernel, 42
- mount, 75–80. *See also* filesystem:
 - mount
- mouse, 303–304
- multitasking, 5–6
- mv, 15

N

- NAT, 216–218
- netcat, 241–242
- netstat, 210–211, 238
- network, 189–191
 - application layer, 191, 229–232
 - client, 210
 - configuration, 193–194, 200–203, 214
 - connection, 210–211, 230, 239–241
 - firewall, 219–221
 - rule, 221–223
 - strategy, 223–224
 - host, 190, 198–199
 - interface, 47, 200–203
 - Internet layer, 191–192
 - layer, 189–192
 - localhost, 205, 209
 - packet, 190–191

- physical layer, 191
- port, 210–211, 230
- prefix, 194
- private, 216–217
- promiscuous mode, 240
- route, 195–196, 198
- router, 190, 192–193, 196–197, 215–216, 218–21
- server, 210, 232–233
- simple, 190, 192–193, 214
- stack, 191
- transport layer, 191–192
- troubleshooting, 197–198, 239–242
- wireless, 202–204
- network configuration manager, 203–206
- NetworkManager, 203–206, 228
- Network Time Protocol (NTP), 158–159, 212
- NFS, 285–286
- nftables, 220
- nice value, 179–180
- nmap, 242–243
- NTP (Network Time Protocol), 158–159, 212

O

- object file, 311
- OOM killer, 86
- open(), 175
- open source, 329
- OpenWRT, 219, 349
- /opt, 41
- OSS, 53

P

- package, 333–334, 338, 341–343
- packet, 190–191
- page, 182
 - fault, 182–183
 - table, 6, 182
- PAGER, 296
- pager, 19, 296
- PAM (Pluggable Authentication Modules), 165–170
- parallel port, 52
- parted, 67–70

- partition, 50
 - alignment, 72
 - altering table, 67–70
 - Apple, 73
 - capacity, 69, 81
 - extended, 68–69
 - geometry, 70–72
 - logical, 68–69
 - primary, 68
 - reading table, 69–70
 - swap, 68–69, 85
 - system ID, 69
 - table, 66–70
 - viewing, 68–69
 - Windows, 73
- passwd, 21, 34, 155–156
- password
 - changing, 21, 170
 - file, 26, 153–155, 164–165, 346
- patch, 339
- patchelf, 317
- path, 16
- PATH, 22–23, 288–290
- path
 - absolute, 16
 - command, 22–23, 288–290
 - relative, 16
- pathname. *See* path
- performance, 171
 - memory, 86
- Perl, 19, 326
- permissions, 30, 33–35
 - bits, 34
 - changing, 34–35
 - default, 35, 291
 - directory, 35
 - execute, 34–35
 - group, 33–35
 - other, 33–35
 - preserving, 38
 - read, 33–35
 - testing, 260
 - user, 33–35
 - world, 33–35
 - write, 33–35
- physical layer, 191, 199–200
- Pico, 25
- PID (process ID), 30–32, 177, 255
- pidstat, 187–188
- ping, 197–198
- pipe, 19, 27, 39
 - named, 47, 53
- pkg-config, 336–338
- Pluggable Authentication Modules (PAM), 165–170
- plymouth, 51–52
- port scan, 242–243
- printing, 52, 307–308
- private network, 216–217
- /proc*, 40, 79–80, 84
- process, 2–4, 30–33, 84
 - accounting, 188
 - background, 32–33
 - blocked, 185
 - child, 175
 - continue, 32
 - ID, 30–32, 177, 255
 - interface, 40
 - list, 30–31
 - management, 5
 - memory, 6, 86, 172
 - monitoring, 187–188
 - open files, 172–174
 - owner, 9, 162–163
 - priority, 179–180
 - starting new, 7
 - status, 31
 - stop, 31–32
 - terminate, 31–32
 - tracking, 172
 - unexpected termination, 86
- .profile*, 292
- prompt (shell), 12–13, 22, 290
- ps, 30–31, 162–163, 183
- pseudodevice, 8
- pseudoterminal, 51
- pulseaudio, 53
- pwd, 19–20
- Python, 325–326

Q

- Qt, 299

R

- Raspberry Pi, 349
- real-time clock, 157
- real user ID (ruid), 162–163
- reboot, 144–145
- redraw display, 33

- regular expressions, 19
- regular file, 33
- relational database, 347
- remote login, 233–237
- renice, 180
- replication, 347
- resource monitoring, 178
- reverse isearch, 33
- RIP, 308
- rm, 16
- rmdir, 17
- root, 9–10
 - directory, 40, 93, 95–97, 99–100
 - prompt, 13
 - running programs as, 42–43
- route, 195, 201–202
- route (network), 195–196, 198
 - configuration, 200–201
- router, 190, 192–193, 196–197, 215–216, 218–219
- RPC, 243
- rsync, 271
 - bandwidth, 277
 - compression, 277
 - copying
 - from remote host, 277
 - to remote host, 271–274
 - exact copy, 273–274
 - excluding files, 275–276
 - verifying transfer, 276–277
- rsyslogd, 151–153
- ruid (real user ID), 162–163
- runlevel, 113
 - System V, 139–142
 - systemd, 129
 - Upstart, 138–139
- run-parts, 143
- runtime
 - information, 41
 - library search path, 316

S

- Samba, 278–285
 - client, 283–285
- sar, 188
- SATA, 59–60
- saved user ID, 163
- /sbin*, 41
- scheduling tasks, 159–161
- SCons, 342
- scp, 237
- screen, 32
- scripting language, 325–327
- SCSI, 50, 58–64
 - disk, 50–51, 59–62
 - generic, 51, 63–64
 - ID, 58–59
 - listing device information, 50, 59, 63
- sector, 71–72
- security, 162–170
 - in command path, 289
 - network, 243–245
- sed, 266–267
- segmentation fault, 30
- serial port, 52
 - USB, 52
- server role, 8–9
- setuid, 34, 78, 162–163
- sftp, 237
- shadow password, 154–155
- shared library, 40, 314–317, 334–335, 337
 - system calls, 174–175
 - trace, 176
- shebang, 249–250, 325
- shell, 12. *See also* Bourne Shell
 - change, 12, 21
 - editing commands, 24
 - prompt, 12–13, 22, 290
 - quoting, 251–253
 - user, 154–155
 - variables, 21–22, 31, 253
 - special variables, 253–255
 - window, 12, 32–33, 51
- shell script, 12, 249–250
 - arguments, 254–255
 - arithmetic, 261, 268, 270
 - conditional, 256–257
 - include, 269
 - limitations, 250, 270
 - loops, 262–263
 - name, 255
 - permission, 250
 - PID, 255
 - reading user input, 269
 - string test, 260–262
- shortcut. *See* symbolic link
- shutdown, 144–145

- signal, 31–32, 264–265
- single-user mode, 96, 113, 146–147
- socket, 246–247
 - device, 47, 247–248
 - Unix domain, 247–248
- solid-state disk (SSD), 72, 91
- sort, 21
- sound, 53
- source code, 310
- special characters, 23–24
- splash screen, 51–52, 94, 96
- SQL, 347
- SSD (solid-state disk), 72, 91
- SSH, 119, 136–137, 233–237
- standard error, 27–28, 33, 160
- standard I/O, 13–14
 - input, 14, 19, 28, 33, 37, 49
 - output, 14, 19, 27–28, 33, 37, 49, 160
 - redirection, 27–28
- startup. *See* boot
- startup file, 287–290
 - example, 293–295
 - order, 291–295
- stat, 89–90
- stat(), 90
- state, 4
- static library, 314
- stderr, 27–28, 33, 160
- stdin, 14, 19, 28, 33, 37, 49
- stdio, 13–14, 310–311
 - redirection, 27–28
- stdout, 14, 19, 27–28, 33, 37, 49, 160
- strace, 137, 174–175
- stream, 19, 27–28, 46–49
 - edit, 266–267
 - ID (in shell), 28
 - I/O, 13–14
 - search, 18–19, 256–257
- su, 42–43
- subnet, 192–195
 - choosing, 216–217
 - mask, 194–195, 201
 - routing between, 215–216
- subshell, 268–269
- sudo, 43, 163
- superblock, 74, 83, 90
- superserver, 237
- superuser. *See* root
- swap, 80, 85–86
 - partitions, 68–69, 85
- swapoff, 85
- swapon, 85
- symbolic link, 35–36
- sync, 77
- /sys. *See* sysfs
- syscall. *See* system call
- sysfs, 45, 47–48, 55, 84
- SYSLINUX, 98
- syslog, 150–153
- system call, 4, 7–8
 - trace, 174–175
- system clock, 157–159
- systemctl, 116, 118, 120–121
- systemd, 112–114
 - activating unit, 120, 123, 128
 - configuration, 117–120
 - creating unit, 122–123
 - deactivating unit, 123
 - dependency, 114–117
 - disabling unit, 123
 - enabling unit, 119–120, 123
 - job, 121–122
 - log, 121
 - mount unit, 81, 114, 118
 - on-demand resource, 124–129
 - operating, 120–122
 - parallel unit activation, 125–127
 - process tracking, 123–124
 - service unit, 114, 119, 127–129
 - socket unit, 127–128, 237
 - specifier, 120
 - startup, 114
 - System V compatibility, 129
 - target unit, 114
 - unit, 114–115
 - file, 118–120
 - instance, 128
 - variable, 120
- system messaging, 151
- system time, 178–179
- System V init, 112–114, 129, 138–143

T

- tail, 21
- tar, 37–39, 269

- TCP, 209–213, 218
 - filtering, 222–224
 - interacting with service, 230–232
- tcpdump, 240–241
- TCP wrapper, 238
- tcsh, 292–295
- telnet, 230, 233, 241, 245
- tempfs, 84
- temporary file, 264–265
- terminal, 51–52. *See also* shell: window
 - controlling, 51
 - device, 51–52
 - virtual, 51–52, 113, 135–136, 300
- test, 256–261
- text editor, 24–25, 295–296
- text search, 18–19
- thrash, 181. *See also* memory:
 - insufficient
- thread, 176–178
- time, 178–179. *See also* CPU time;
 - elapsed time; system time
- time (of day), 157–159
- time slice, 5
- /tmp*, 41
- toolkit, 299
- top, 172, 178–179
- touch, 15
- traceroute, 198
- transport layer, 209. *See also* network,
 - application layer
- troubleshooting, 151–153
- tune2fs, 77

U

- udev, 45, 48–50, 53–58
 - configuration and rules, 55–56
 - event, 55, 58
- udevadm, 48–50, 57–58, 70
- udev, 53–58, 77
- udisks-daemon, 58
- UDP, 209, 212, 218, 240
- UEFI, 97–98, 105–108
 - ESP, 108–109
 - secure boot, 106
- uevent, 55, 58
- umask, 35, 291
- umount, 76–77

- Unix, 11
- Unix domain socket, 247–248
- unlinking, 89. *See also* files: deleting
- unxz, 39
- unzip, 39
- Upstart, 112–113, 130
 - configuration, 133–135
 - event, 112, 130–131, 133–135, 137
 - job, 130–133, 137–138
 - log, 134, 138
 - mounting filesystems, 130–131,
 - 133–134
 - operation, 137–138
 - process tracking, 136–137
 - runlevel, 138–139
 - startup, 130–131
 - System V compatibility, 138–139
- uptime, 180
- USB, 61–62
 - listing device information, 62
 - relationship to SCSI, 50, 60–62
 - serial port, 52
- user, 9–10
 - authentication, 164–170
 - authorization, 164
 - changing, 42–43
 - environment, 287–288
 - ID, 9, 153–155, 162–164
 - identification, 164–165
 - management, 154–157
 - mode, 3
 - process (*see* process)
 - regular, 12
 - root (*see* root)
- user space, 2–3
 - filesystem, 73
 - interface, 90–91
 - organization, 8–9
 - start, 93, 95–96, 111–112
- userland. *See* user space
- username, 9, 153–155
- /usr*, 41–42
- /usr/lib*, 314
- /usr/local*, 41, 334, 338
- /usr/share*, 41
- UTC, 157–158
- UUID, 50, 76–77, 79, 96, 99–101

V

- /var*, 41
- /var/log*, 151–153
- VFS, 73, 90
- vi, 24–25
- vipw, 155–156
- virtual console, 51–52, 113,
135–136, 300
- virtual machine, 327, 347–348
- virtual memory, 6, 85. *See also*
memory: management
- vmstat, 183–185

W

- wallpaper. *See* desktop background
- warning messages, 29
- Wayland, 305
- web application, 346
- web server, 271, 346
- WEP, 228
- while, 262–263
- who -r, 113
- widget, 299
- wildcard. *See* glob
- window manager, 298–299
- Windows
 - boot, 106–107
 - file sharing, 278–285
 - partition, 73
 - password, 280–281
 - printer sharing, 283
- wireless network, 202–204. *See also*
Ethernet: wireless
- worker process, 232–233
- WPA, 228

X

- xargs, 267–268
- xev, 302
- X event, 301–302
- xinetd, 237
- xinput, 303–304
- XKB, 304
- xlsclients, 301
- xmodmap, 302, 304
- xset, 305
- X Window System
 - application, 299
 - client, 298, 301
 - diagnostics, 301–305
 - display (*see* display)
 - event, 301–302
 - future, 305
 - input, 302–304
 - network transparency, 300–301
 - preferences, 302–305
 - server, 51, 298–300
 - tunneling, 233–234, 301
 - window manager, 298–299
- xwininfo, 301
- xz, 39

Y

- Yacc, 324–325

Z

- zcat, 39
- zip, 39

How Linux Works, 2nd Edition is set in New Baskerville, TheSansMono Condensed, Futura, and Dogma. The book was printed and bound by Edwards Brothers Malloy in Ann Arbor, Michigan. The paper is 60# Husky Opaque, which is certified by the Sustainable Forestry Initiative (SFI).

The book uses a RepKover binding, in which the pages are bound together with a cold-set, flexible glue and the first and last pages of the resulting book block are attached to the cover with tape. The cover is not actually glued to the book's spine, and when open, the book lies flat and the spine doesn't crack.